

TFR26 Spy

GENERAL CHARACTERISTICS

Wet / White Wet Inlay dimensions: 24 x 15 mm

—Antenna dimensions: 22 x 13,5 mm

Standard pitch: 21,6 mm

Operating frequency: Global (860 - 960 MHz)

Chip: IMPINJ Monza R6 / R6P

EPC Memory: 96 / 128 bits auto serialized

USER Memory: NA / 32 bits

TID Memory: 64 bit with 48 bit unique serial number

Inlay substrate material: PET

Inlay-to-liner adhesive: SH3020 (Arconvert)

Liner material: CC62 (Arconvert)

Total thickness over chip: 170 microns

Standard web width: 52 mm

Unwind direction: Label side out

RF Protocol: ISO-18006-C, EPC Class 1, Gen 2

RoHS: EU Directive 2011/65 EU Compliant

Quality assurance: 100% read tested with

out-of-tolerance inlay marked

Operating temperature: -40°C to 85°C

COMMON APPLICATIONS

Pharmaceutical and healthcare industries.

Jewellery, cosmetics and other retail item-level.

Supply chain.

Minimum order quantity: 10,000 pcs. Average of units per roll: TBD

The TFR26 Spy is an RFID tag **appropriate for pharmaceutical and healthcare industries solutions** because of its size and range. It also **suits jewellery, cosmetics and other retail item-level RFID deployments**. Finally, it's also a good choice for the supply chain.



CARE AND HANDLING RFID inlays are sensitive to ESD. Observe standard practices to keep environmental static charge to a minimum. APPLICATIONS This product should be tested by the customer/user thoroughly under end use conditions to ensure the product meets the requirements. Trace-ID does not represent that this product is fit for any purpose or use. PRODUCT CHANGES Trace-ID reserves the right to modify, change, supplement or discontinue product offerings at any time without notice. © 2018 Trace-tech Id Solutions S.L. All rights reserved.

